

LINED DOUBLE WINDOW SIGHT GLASS



Application:

- | | |
|-----------------------|-------------------------|
| 1. Food and Dairy | 6. Pulp and paper |
| 2. Marine industry | 7. Petroleum / Refinery |
| 3. Process equipment | 8. Chemical process |
| 4. Electric utilities | 9. Fertilizer |
| 5. Pharmaceuticals | 10. Steel |

Specification:

Design Standard
Flange To Flange Distance
End Connection

:ASME B 16.34
:As Per ASME B 16.10 / DIN EN 558-I
:Flanged End to ASME B 16.5,150#
:BS 10 Table D / E / F / H
:PN 6 / PN 10 / PN 16
:DIN/ JIS/ IS Standard
:1" (DN25) to 6"(DN 150)
:150# / PN10 / Pn16

Manufacturing Size Range
Pressure Rating of Valve

Sizes available from 25NB to 300NB

Our Other Products:



Stainless Steel Double Window Sight Glass



Double Window Jacketed Sight Glass

- Designed to observe flow of corrosive media
- High Visibility hence Easy and Quick Inspection
- Suitable upto 200 deg.C (PFA lined Sight Glass)
- Easy replacement of glass without dis-mantling complete sight glass
- Toughened Borsilicate Glass
- Durable construction / Manufactured to the highest standard
- Tailor made design (Make to order face to face dimension)
- No rotating parts-No maintenance
- All wetted parts are of PTFE and Toughened Glass

PTFE Lined Tubular / Full View Sight Glass



ISO 9001:2015
BUREAU VERITAS
Certification



Noble Glass Works Pvt. Ltd.

E-mail : info@nobleglass.in
Contact : 0265 - 2574839